

T-Series is an open-cell polyether-based polyurethane foam, that demonstrates cost effective utility for general industrial, footwear, automotive, and flexographic printing applications. Available in a broad range of density, firmness, and thickness options, T-Series provides designers, converters, and fabricators with versatility and function. The T-Series family of foams are breathable, dimensionally stable, and readily thermoformable with a multitude of color and functional additive options.

## HYPUR-CEL<sup>®</sup> T-SERIES TYPICAL PROPERTIES

Product	Density (pcf) ASTM D3574	CD 25% (psi) ASTM D1056	C Set (%) ASTM D1056	Tensile Strength (psi) ASTM D412	Elongation (%) ASTM D412
T0503	5	3	3 max	69	123
T0507	5	7	3 max	70	85
T0805	8	5	3 max	70	145
T0812	8	12	3 max	90	60
T0820	8	20	8 max	124	50
T1015	10	15	3 max	125	115
T1505	15	5	3 max	65	220
T1515	15	15	3 max	130	145
T1520	15	20	3 max	165	145
T2040	20	40	3 max	230	140

### Product Availability

Standard 60 inch (1.52 meter) wide rolls with capabilities to produce in various widths.  
 Available in 50 feet (15.24 meters) and 100 feet (30.48 meters) lengths, skived to custom thicknesses.  
 Available with adhesives, laminated fabrics, films, custom coatings or composites.  
 Various color options available with the ability to custom color match using our fully reacted colorants.  
 Other additives, such as anti-microbial and flame retardants, are available depending on sales opportunity and volume.

### Product stewardship declarations available upon request for:

ROHS | REACH | Prop 65 | Berry Amendment | Latex Free

**WE PRODUCE EXCELLENCE**

EXCELLENT PRODUCTS | EXCELLENT SERVICE | EXCELLENT PEOPLE

[rubberlite.com](http://rubberlite.com)



2501 Guyan Avenue | Huntington, WV 25703  
 304.525.3116

ISO 9001 Certified

**Rubberlite**  
 Incorporated